



impulse  **powertek**

SIGNALING TOWER LIGHTS

Signaling Units Ø60



TOWER LIGHT

- *Designed to communicate, application status, alerting your critical equipment.*
- *It helps and monitor the most challenging of your machine applications and control panel .*
- *It is easy to install and it offers steady LED Technology*
- *It provide highly visible steady light to indicate areas of required attention.*
- *Up to 3 colors in one device.*
- *It can be pre-assembled to save time for application needs or ordered as separate lights.*
- *It is almost maintenance - free and needs only little space.*

TECHNICAL DATA		1 TIER	2 TIER	3 TIER
Model		T61	T62	T63
Supply Voltage		24V AC/DC	24V AC/DC	24V AC/DC
Current Consumption		55mA per Unit	55mA per Unit	55mA per Unit
		1 (Red, Amber, Green, Blue ,Multi)	2 (Red, Amber, Green,Blue)	3 (Red, Amber, Green , Blue)
Buzzer	Level Style	No / Yes	No / Yes	No / Yes
	Supply Voltage	24V AC/DC	24V AC/DC	24V AC/DC
	Sound Level	80±5 dB	80±5 dB	80±5 dB
	Current	40mA per Unit	40mA per Unit	40mA per Unit
Wire Length		500mm	500mm	500mm
Function		Steady	Steady	Steady
Mounting Type		Screw	Screw	Screw
Ambient Temperature		-25 °C to +60 °C	-25 °C to +60 °C	-25 °C to +60 °C
Storage Temperature		-25 °C to +60 °C	-25 °C to +60 °C	-25 °C to +60 °C
Dimension		220mm x Ø 70mm	265mm x Ø 70mm	300mm x Ø 70mm
Weight		210 grams	265 grams	320 grams
In the pack		Tower lamp + Specification sheet	Tower lamp + Specification sheet	Tower lamp + Specification sheet

ORDERING INFORMATION

- Number Of Tiers**
 - 1 - One Tier
 - 2 - Two Tier
 - 3 - Three Tier
 - 4 - Four Tier

- Type**
 - T Series
 - TA Series

- Lens Dia**
 - 4 - 45mm
 - 6 - 65mm

- Buzzer**
 - N - Without
 - H - With (Not Available in 45mm)

- Body Colour**
 - G - Gray
 - B - Black

- Lens Colour**
 - C - Colour (Same AS LED Colour)
 - T - Transparent

- LED Colour**
 - R - Red
 - A - Amber
 - G - Green
 - B - Blue

- Supply**
 - 2 - 24VAC / 24VDC

- Mount**
- Stem Length**

- | | | |
|------------|-----------------------|-------------|
| | Swivel | Stem |
| N - | No | No |
| S - | No | Yes |
| V - | Yes | No |
| E - | Yes | Yes |
| D - | Direct Mount | |
| L - | Stem With 'L' Bracket | |

- 0 - No Stem
 - 1 - 75mm
 - 2 - 200mm
 - 3 - 300mm
- (*Applicable in S,E and L Mount Only)



Example : T63 - HGE1C2-RAG

- 6...Lens Dia...60mm
- 3...No Of Tiers...3 Tiers
- H...Buzzer...With Buzzer
- G...Body Colour...Gray
- E...Mount... Swivel With Stem
- 1...Stem Length...75mm
- C...Lens Colour...coloured Lens
- 2...Supply...24VAC/VDC
- RAG...LED Colour...Red,Amber,Green



CORPORATE OFFICE :

103 , Anand Mangal III , Opp. Doctor House,
Ambawadi, Ahmedabad , Gujarat - 380006

Ⓔ info@impulsepowertek.com Ⓓ 079 - 2640 2883 Ⓜ +91 - 99250 10468

Ⓜ www.impulsepowertek.com

UNIT 1:

C/22, Maruti Industrial Estate , Nr choksi Tube,Phase 1,
G.I.D.C Vatva , Ahmedabad - Gujarat (India.) - 382445

Ⓔ info@impulsepowertek.com Ⓓ 079 - 4008 5952 Ⓜ +91 - 99250 10468

Ⓜ www.impulsepowertek.com

UNIT 2:

Plot No.1222, Phase - 3, Nr . V Trans
G.I.D.C Vatva , Ahmedabad - Gujarat (India.) - 382445

Ⓔ info@impulsepowertek.com Ⓜ +91 - 98250 40151 Ⓜ +91 - 99250 10468

Ⓜ www.impulsepowertek.com